

380 V to 54 V DC-DC powercore

Using the Flatpack2 DCDC 380/48 3000 SHE module with Eltek's feature-rich Smartpack2 control and monitoring unit enables sites to benefit from utilizing 380 V_{DC} as a transmission voltage, either for a competitive alternative to traditional UPS in Data Centers, or for central power plants in Telecom site expansions.



Flatpack2 DCDC 380V 54V Powercore

12 kW, and 24 kW capacities inc. distribution

Doc M30806.404.DS3 – rev1.1

DESCRIPTION

CONVERTER SYSTEM

Integrating state-of-the-art, super high efficiency converter modules with Eltek's feature rich Smartpack2 monitoring and control unit, the high performance Flatpack2 DCDC 380V 54V Power System converts the 380 V_{DC} bus voltage down to a regulated 54 V_{DC} with a module efficiency of 98.2 %.

This enables the advantages of DC power systems of reliability, modularity, redundancy and higher end-to-end efficiency to be fully utilized to ensure optimal power availability in sites traditionally using AC power.

For Telecom expansion sites, greater site flexibility, and distances, can be achieved between the central power system and the load, while using substantially less cabling infrastructure.

APPLICATIONS

TELECOM

- Telecom central office expansions
- High power site upgrades

DATA CENTERS

- Conversion from 380 V_{DC} (260-400 V_{DC}) to 50-55 V_{DC}
- Colocation facilities
- UPS+VDC plant replacement

KEY FEATURES

- INPUT PROTECTION
- VERSATILITY
- SCALABILITY
- MODULAR – BUILD AS YOUR LOAD GROWS
- SUPER HIGH EFFICIENCY
- SMARTPACK2 CONTROLLER
- HOT PLUGGABLE
- 50-55 V_{DC} ADJUSTABLE OUTPUT
- PATENTED SHE TECHNOLOGY



Flatpack2 DCDC 380V 54V Powercore ELTEK

A Delta Group Company

Doc: M30806.404.DS3 – rev1.1

Model	12 kW Powercore	24 kW Powercore
Part number	M30405.402	M30806.404
INPUT DATA		
Voltage (operating range)	260 - 400 V _{DC}	
Maximum current	49.2 A	98.4 A
Protection (module level)	Fuse, shutdown when V _{IN} is out of range	
OUTPUT DATA		
Voltage (default)	54.5 V _{DC}	
Voltage (adjustable range)	50 - 55 V _{DC}	
Max power, nominal input	12 kW	24 kW
Max current, @V _{OUT} = 50 V _{DC}	240 A	480 A
Current sharing	±5 % of maximum current from 10 to 100 % load	
Static voltage regulation	±0.5 % from 0 – 100 % load and nominal input	
Dynamic voltage regulation	±5.0 % for 10-90 % or 90-10 % load variation, regulation time < 50 ms	
DC Outputs	Up to 18 ways ≤63 A MCB Up to 12 ways ≤125 A MCB Or a combination of ≤63 A and ≤125 A	
Protection	Overvoltage shutdown; short circuit proof; high temperature; hot plug-in inrush current limiting; OR-ing FET	
Additional info	See Flatpack2 DCDC 380V 48V 3000W SHE datasheet	
CONTROL AND MONITORING		
Monitoring unit	Smartpack2	
Local Operation	Display and keys, WEB interface via standard browser	
Remote Operation	WEB interface; MODBUS; SNMP protocol and email	
Alarms	Low & high output voltage alarms (Minor and major levels), Earth fault alarm, Temperature alarm, Mains outage alarm, Load breaker tripped alarm and much more.	
Additional info	See Smartpack2 datasheet	
OTHER SPECIFICATIONS		
Peak Efficiency	98.2 %	
Isolation	4.2 kV _{DC} – input and output 2.2 kV _{DC} – input earth 0.5 kV _{DC} – output earth	
Operating temperature	-20 to +45 °C (-4 to +113 °F) possible power derating above 40 °C (104 °F)	
Storage temperature	-40 to +85 °C (-40 to +185 °F)	
Humidity	5 – 95 % RH, non-condensing	
Dimensions [WxHxD]	482 x 222 (5U) x 383 mm (19 x 8.8 x 15")	482 x 267 (6U) x 383 mm (19 x 10.5 x 15")
DESIGN STANDARDS		
Electrical safety	IEC/EN 60950-1: 2013	
EMC	IEC/EN 61000-6-1:2007, IEC/EN 61000-6-2:2005, IEC/EN 61000-6-3:2007 + A1:2011, IEC/EN 61000-6-4:2007 + A1:2011, ETSI EN 300 386 v2.1.1: 2016	
Environment	Tested in accordance with: ETSI EN 300 019-2-1 v2.2.1: 2014 (Class 1.2); ETSI EN 300 019-2-2 v2.3.1: 2013 (Class 2.3); ETSI EN 300 132-3-1 v2.1.1; 2011/65/EU (RoHS) & 2008/98/EC (WEEE) Normal operating conditions as per IEC/EN 62040-5-3:2016 clause 4.2, other operating conditions as per clause 4.3 must be advised.	

1) Cabinet views shown without doors.

Doc M30806.404.DS3 – rev1.1

Specifications are subject to change without notice